

KBL12400 12V 38Ah



The KAISE LONG LIFE Series 10 years has been designed for different applications, such as UPS, electric and telecommunications applications that require a long useful life.




Performance Characteristics

Nominal Voltage	12V	
Dimensions	Length (mm / inch)	197 / 7.76
	Width (mm / inch)	165 / 6.50
	Height (mm / inch)	170 / 6.69
	Total Height (mm / inch)	170 / 6.69
Approx. Weight (Kg / lbs)	13.2 / 29.1	
Design Life	10 years	
Terminal	M6	
Container Material	ABS	
Rated Capacity	40.6Ah / 2.03A	(20hr, 1.80V / cell, 25°C / 77°F)
	38.0Ah / 38.0A	(10hr, 1.80V / cell, 25°C / 77°F)
	33.1Ah / 6.61A	(5hr, 1.75V / cell, 25°C / 77°F)
	23.6 Ah / 23.6A	(1hr, 1.60V / cell, 25°C / 77°F)
Max. Discharge Current	456A (5s)	
Internal Resistance	Approx 10.0mΩ	
Operating Temp. Range	Discharge : -15 ~ 50°C (5 ~ 122°F)	
	Charge : 0 ~ 40°C (32 ~ 104°F)	
	Storage : -15 ~ 40°C (5 ~ 104°F)	
Nominal Operating Temp. Range	25 ± 3°C (77 ± 5°F)	
Cycle Use	Initial Charging Current less than 11.4A.	
	Voltage: 14.4VPC ~ 15.0VPC at 25°C (77°F)	
	Temp. Coefficient: -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5VPC ~ 13.8VPC at 25°C (77°F)	
	Temp. Coefficient: -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Fully charged Kaise Long Life Series batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

Constant Current Discharge (Amperes) at 77°F (25°C)

Volts/cell	10min	15min	30min	1h	3h	5h	10h	20h
1.80V	50.9	42.0	29.9	19.2	9.50	6.46	3.80	2.03
1.75V	57.8	47.3	32.5	20.9	9.88	6.61	3.90	2.08
1.70V	65.3	52.5	35.5	22.1	10.4	6.99	4.05	2.14
1.65V	70.1	56.2	37.4	22.9	10.8	7.21	4.17	2.20
1.60V	77.1	61.6	39.9	23.6	11.1	7.39	4.25	2.24

Dimensions and Terminal (Unit: mm (inches))



Applications

- UPS
- Telecommunications equipment
- Solar energy systems
- Cable TV
- Power station
- Marine equipment
- Military equipment
- Emergency power systems
- Railway systems

Certifications

ISO 9001:2008 ISO 14001:2008



Discharge Current vs. Discharge Voltage


Final discharge voltage V/CELL	1.8	1.75	1.7	1.6
Discharge current (A)	$I \leq 0.1CA$	$0.25CA \geq I > 0.1CA$	$0.55CA \geq I > 0.25CA$	$I > 0.55CA$

Constant Power Discharge (Watts per cell) at 77°F (25°C)


Volts/cell	10min	15min	30min	1h	3h	5h	10h	20h
1.80V	93.9	78.1	56.7	37.2	18.6	12.7	7.58	4.06
1.75V	104.9	87.0	61.1	40.3	19.3	13.0	7.78	4.16
1.70V	115.9	95.2	66.3	42.5	20.2	13.7	8.07	4.26
1.65V	123.3	101.1	69.4	43.7	21.0	14.1	8.29	4.39
1.60V	132.6	109.0	73.6	44.8	21.4	14.4	8.45	4.45

(Note) The above characteristics data are average values obtained within three charge/discharge cycles not the minimum values.


Charging Characteristics (float use)




Cycle Life in Relation to Depth of Discharge




Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Self Discharge Characteristics



- A** No supplementary charge required (carry out supplementary charge before use if 100% capacity is required)
- B** Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25 CA and constant voltage 2.25V / cell.
 2. Charged for above 20 hours limited current 0.25CA and constant voltage 2.45V / cell.
 3. Charged for 8-10 hours at limited current 0.05 CA.
- C** Supplementary charge often fail to recover the capacity. The battery should never be left standing till this is reached.

IMPORTANT NOTE: The specifications presented herein are subject to revision without notice.