

Product data sheet

Specifications



APC Smart-UPS On-Line, 3kVA, Rack/Tower, 120V, 8x 5-20R+1x L5-30R NEMA outlets, SmartSlot, Extended runtime, W/O rail kit, TAA

SRT3000XLAUS

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	2700 W
Rated Power In Va	3000 VA
Input Connection Type	NEMA L5-30P
Output Connection Type	8 NEMA 5-20R 1 NEMA L5-30R
Cable Length	10 ft (3.05 m)
Number Of Cables	1
Provided Equipment	CD with software Documentation CD Installation guide Removable support feet USB cable Warranty card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	Lead-Acid battery
Included Battery Modules	1
Typical Recharge Time	3 h
Rbc Quantity	1
Battery Charge Power (Watts)	151 W rated
Battery Life	3...5 year(s)
Replacement Battery	APCRBC152
Extendable Run Time	1

General

Topology	Double Conversion Online
Product Web Sub-Family	TAA compliance

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	3.35 in (8.5 cm)
Depth	25.00 in (63.5 cm)
Net Weight	69.00 lb(US) (31.3 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	Yes
Mounting Position	Vertical

Input

Input Frequency	40 - 70 Hz auto-sensing
-----------------	-------------------------

Output

Maximum Configurable Power In Va	3000 VA
Max Configurable Power (Watts)	2700 W
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains
Waveform Type	Sine wave
Harmonic Distortion	Less than 2%
Crest Factor	3 : 1
Bypass Type	Internal Bypass (Automatic and Manual)

Conformance

Product Certifications	TAA compliance ENERGY STAR V2.0 (USA)
------------------------	--

Environmental

Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Acoustic Level	55 dBA
Heat Dissipation	805 Btu/h

Ip Degree Of Protection	IP20
-------------------------	------

Communications & Management

Free Slots	1
------------	---

Alarm	Audible and visible alarms : prioritized by severity
-------	--

Emergency Power Off (Epo)	Yes
---------------------------	-----

Surge Protection and Filtering

Surge Energy Rating	340 J
---------------------	-------

Ordering and shipping details

Gtin	731304340478
------	--------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	9.69 in (24.6 cm)
------------------	-------------------

Package 1 Width	34.29 in (87.1 cm)
-----------------	--------------------

Package 1 Length	23.58 in (59.9 cm)
------------------	--------------------

Package 1 Weight	81.00 lb(US) (36.74 kg)
------------------	-------------------------

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product


 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Environmental Certifications

 Energy Star® [ENERGY STAR UPS V2.0 \(USA\)](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant with Exemptions](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
